USMS POOL LENGTH REPORTING FORMS

For initial pool length certification as well as pool length confirmation for bulkhead pools

Maintaining pool length certification forms is an LMSC responsibility. Completed forms shall be sent to the LMSC Top Ten Recorder. If a pool being considered for a sanctioned or recognized competition is **NOT** on file with the USMS National Swims Coordinator, the **Pool Length Certification Form** should be submitted prior to competition (ideally before it is sanctioned or recognized). To add the pool to the USMS List of Measured Pools, email the **Pool Length Certification Form** to the National Swims Coordinator, records@usmastersswimming.org.

There are two constructions of Racing Courses (defined under USMS rules 106.3.1 and 106.3.2):

- Permanent Course Walls (106.3.1) means the start/turn walls are FIXED and cannot be moved. These pools require a one-time measurement for <u>Certification</u> that the pool is in compliance with USMS Facility Standards 106.2.1 for times to be considered for USMS and World Aquatics top ten and records. The Pool Length Certification Form should be submitted for certification with every lane being measured.
- Non-Permanent Course Walls (106.2.1 F and 106.3.2) with one or more movable walls (aka "movable bulkheads") means that one or more of the course walls (start and/or turn) is NOT permanent. The Pool Length Certification Form must be used when submitting a pool of this type for <u>Certification</u> once originally, AND in addition the Bulkhead Placement Confirmation form must then be submitted for <u>each</u> competition if the times are to be considered for USMS Records and Top 10.

Pool Length Measurement Information:

- It is permissible to use existing certification documents on file with USMS, or World Aquatics if all the lanes have been measured and are in compliance with USMS Facility standards.
- Measurement devices must meet the following standards:
 - Have a minimum measuring quality of a steel tape for the entire course length.
 - Laser devices meeting this standard are permissible.
 - The accuracy of the measuring device must be at least +/- .005m, +/- 0.20 inch, or +/- 0.016 foot. This tolerance refers to the tolerance of the measuring device only.
 - 2 or more measuring tapes shall **NOT** be combined to perform the measurement.
- Frequency of measurement for **Permanent courses**:
 - For initial certification, one measurement must be conducted on each competition lane.
 - After initial certification, re-measurement is **NOT** required unless structural changes, including resurfacing, take place.
- Frequency of Measurement for Non-Permanent Courses (aka "movable bulkhead" pools):
 - For initial certification use the **Pool Length Certification Form.** One measurement must be completed on each competition lane.
 - Thereafter, for events sanctioned and/or recognized by USMS, a course length equal to or greater than the minimum required length must be confirmed before competition begins AND at the conclusion of each session. Confirmation measurement includes measuring each outside lane and one of the center lanes. A session is any portion of a meet distinctly separated from other portions of the meet by locale, time, day or type of competition; i.e. first day and second day, morning and evening, etc., exclusive of a short break between events such as before the start of distance events or relays.
 - World Aquatics measurement rules and policies shall be the standard for events sanctioned by World Aquatics Masters member federations other than USMS. Currently, World Aquatics does not require course length confirmation for either World Aquatics Top 10 or records.
 - The measurement rules and policies of USA Swimming shall be the standard for Top 10 eligibility for events sanctioned or approved by USA-S. Currently, USA-S only requires course length confirmation for

national records. Therefore, times achieved by USMS members at USA-S sanctioned meets are eligible for Top 10 consideration without length verification. A bulkhead placement course confirmation measurement <u>is required for a USMS record</u> set at events sanctioned or approved by USA-S. For dual sanctioned events, USMS measurement rules and policies shall apply, so course length confirmation must be performed in accordance with USMS standards for times to be considered for USMS Top 10 and records.

For times from USMS sanctioned or recognized competition to be considered for USMS and World Aquatics (formerly known as FINA) Top 10 and records, the course length must comply with USMS Facility Standards as defined in Article 106 (2023 USMS Rule book).

Minimum Measurement lengths:

- Measurements (certifying or confirming) may be conducted with or without touchpads in place.
- If touchpads are NOT in place, the measurement must be taken in the center of the lane at water level. If a protrusion exists where the touchpad would be placed, the protrusion must be used as a measuring point.
- If touchpads are in place, measure from the face of the touchpad in the center of the lane at water level to the other end of the course.
- The minimum measured course length during competition shall be as follows:
 - SCY 25 yards, 75.00 ft, or 75 ft 0 in or 75' 0"
 - SCM 25 meters, 82.02 ft, or 82 ft 0.24 in or 82 ft 1/4 in or 82' ¼"
 - \circ LCM 50 meters, 164.04 ft, or 164 ft 0.5 in or 164 ft 1/2 in or 162' $\frac{1}{2}$ "
- Courses measured with no touchpads in place AND will have one touchpad in place for competition must be at least the following measured lengths:
 - SCY: 25.01 yards, 75.03 ft, or 75 ft 3/8 in or 75' 3/8"
 - $\,\circ\,$ SCM: 25.01 meters, 82.05 ft, or 82 ft 0.6 in or 82 ft 5/8 in or 82' 5/8"
 - LCM: 50.01 meters, 164.08 ft, or 164 ft 1 in or 164' 1"
- Courses measured with no touchpads in place AND will have two touchpads in place during competition must be at least the following measured lengths:

0	SCY:	25.02 yards,	75.06 ft, or	75 ft ¾ in or	75′ ¾″
0	SCM:	25.02 meters,	82.10 ft, or	82 ft 1.2 in or	82 ft 1 1/8 in or 82'1 1/8"
0	LCM:	50.02 meters,	164.11 ft, or	164 ft 1.3 in or	164 ft 1 3/8 in or 164' 1 3/8"

Special comments:

- When using a laser, ensure that the device is set properly to compensate for the length of the measuring device (typically about 6"). Measurement lengths that exceed the minimum lengths above by more than 2" should be re-confirmed before submitting any forms.
- Additional information can be found on the Records and Tabulation section or the Event management section of the USMS Guide to Operations. <u>when to measure pools.pdf (azurefd.net)</u>

Pool Length Certification Form (rev. 11/2/2023)

Submit this form for either of the following conditions: a) the pool is not on the list of USMS Measured Pools or b) the pool has undergone renovation to any portion of the pool where starts and/or turns will take place.

Only this page needs to be submitted for your pool certification.

Pool Name			Course measured (check one)	
Address				
City	State	Zip	25 Meters	
LMSC			50 Meters Bulkhead (check one) YesNo	
	h multiple pools, please identify t we pool name within the facility o vithin the entire facility.			
b. Distances meas feet w feet an meters		d as a fraction to 1/8 like 75 scimal to 1/100 like 50.01m		
Date of Measurem		neasured:wall-to-wal	l,pad-to-pad,wall-to-pad	
Date of Measurem Be sure	ent: How n e to include fractions or decim	neasured:wall-to-wal		
Date of Measurem Be sure Lane 1	ent: How n e to include fractions or decim Lane 2	neasured:wall-to-wal al places. Lane 3	Lane 4	
Date of Measurem Be sur- Lane 1 Lane 5	ent: How n e to include fractions or decim Lane 2 Lane 6	neasured:wall-to-wal al places. Lane 3 Lane 7	Lane 4 Lane 8	
Date of Measurem Be surv Lane 1 Lane 5 Lane 9	ent: How n e to include fractions or decim Lane 2 Lane 6 Lane 10	neasured:wall-to-wal al placesLane 3 Lane 7Lane 11	Lane 4 Lane 8 Lane 12	
Date of Measurem Be surv Lane 1 Lane 5 Lane 9 Lane 13	ent: How n e to include fractions or decim Lane 2 Lane 6 Lane 10 Lane 14	neasured:wall-to-wal al places. Lane 3 Lane 7 Lane 11 Lane 15	Lane 4 Lane 8 Lane 12 Lane 16	
Date of Measurem Be surv Lane 1 Lane 5 Lane 9 Lane 13 Lane 17	ent: How n e to include fractions or decim Lane 2 Lane 6 Lane 10 Lane 14 Lane 18	neasured:wall-to-wal al places. Lane 3 Lane 7 Lane 11 Lane 15	Lane 4 Lane 8 Lane 12	
Date of Measurem Be surv Lane 1 Lane 5 Lane 9 Lane 13 Lane 17	ent: How n e to include fractions or decim Lane 2 Lane 6 Lane 10 Lane 14 Lane 18	neasured:wall-to-wal al places. Lane 3 Lane 7 Lane 11 Lane 15 Lane 19	Lane 4 Lane 8 Lane 12 Lane 16 Lane 20	
Date of Measurem Be sure Lane 1 Lane 5 Lane 9 Lane 13 Lane 17 Lane 21	ent: How n e to include fractions or decim Lane 2 Lane 6 Lane 10 Lane 14 Lane 18 Lane 22	neasured:wall-to-wal hal places. Lane 3 Lane 7 Lane 11 Lane 15 Lane 19 Submitted by:	Lane 4 Lane 8 Lane 12 Lane 16 Lane 20	
Date of Measurem Be sure Lane 1 Lane 5 Lane 9 Lane 13 Lane 17 Lane 21	ent: How n e to include fractions or decim Lane 2 Lane 6 Lane 10 Lane 14 Lane 18 Lane 22	neasured:wall-to-wal hal places. Lane 3 Lane 7 Lane 11 Lane 15 Lane 19 Name	Lane 4 Lane 8 Lane 12 Lane 16 Lane 20	
Date of Measurem Be survey Lane 1 Lane 5 Lane 9 Lane 13 Lane 17 Lane 21 4. Measured by: Name Title	ent: How n e to include fractions or decim Lane 2 Lane 6 Lane 10 Lane 14 Lane 18 Lane 22	neasured:wall-to-wal al places. Lane 3 Lane 11 Lane 15 Lane 19 Name Title	Lane 4 Lane 8 Lane 12 Lane 16 Lane 20	

Completed forms should be sent to the Top Ten Recorder of the LMSC. Attach a copy of this form to record applications if the form is not already on file with the USMS National Swims Coordinator. To add the pool to the USMS List of Measured Pools, email a copy of this form to Mary Beth Windrath, National Swims Coordinator, records@usmastersswimming.org. Measure before applying for a sanction.

Bulkhead Placement Confirmation (rev. 11/2/2023)

This form assumes that the Pool Length Certification Form is already on file with USMS. Submit this form to confirm a course that has non-permanent wall(s). Only this page needs to be submitted for your bulkhead placement confirmation.

1. Facility (*See Note)

25 Yards
25 Meters
50 Meters

Laser

Other

*Note: For facilities with multiple pools, please identify the specific pool being measured either by unique pool name within the facility or the pool location in relation to other pools within the entire facility.

2. Measurement parameters (check one)

a. Measuring device (see instructions): Steel tape____

- b. Distances measured in (check one):
 - feet with feet displayed as a decimal to 1/100 like 75.01 feet
 - feet and inches with inches displayed as a fraction to 1/8 like 75ft 3/8 in. or 75' 3/8"
 - meters with meters displayed as a decimal to 1/100 like 50.01m
 - meters and centimeters with centimeters displayed separately as 50m 1cm
- 3. Bulkhead Placement Confirmation Measurements (per Article 105.1.7) Measure the outermost lanes and a center lane **BEFORE** the meet **AND** after each Session. Include **how** it was measured: wall-to-wall, or pad-to-pad, or wall-to-pad.

	Pre-meet	Post Session 1	Post Session 2	Post Session 3	Title
Date					Phone Number
Left Outer					Email
Left Outer					
Lane #					5. Submitted by:
Left Outer					S. Submitted by:
Lane Length					Namo
Center					Name
Lane #					Title
Center					Phone Number
Lane Length					
Right Outer					Email
Lane #					
Right Outer					A copy of this form from the beginning of the meet
Lane Length					and after each session must be included with meet
0) wall-to-wall?	1				results sent to the LMSC Top Ten Recorder in order to confirm bulkhead placement. For a record
1) wall-to-pad?					application, this form should be attached to and
2) pad-to-pad?					submitted with the Record Application form.

4. Measured by: